

FLEX LUBE X-TREME

DESCRIPTION

Flex Lube X-treme is a lubricant based on a very pure base oil with very low amount of impurities that often are harmful for the environment and the user. It has very good anti-corrosion properties and thermal stability. It is moisture repellent and its low viscosity offers unique running characteristics.

Food grade PTFE (NSF H1) is added to further increase its lubricating properties and enhancing the product's eco-friendly character. Meets the requirements of Green World.



PROPERTIES

- Unique lubrication power due to the special mixture of oil and food grade PTFE.
- The product can be used at running machines, e.g. not only when machine stops.
- Even wire ropes can be treated with this grease.
- Offers slide protection and above all rust protection.
- Due to the excellent adhesiveness the economical effect can be stressed.
- Green World classified.
- Green certified propellant with CO2 reduction up to 90%, naturally produced via organic waste = Green Propellant.

FIELD OF APPLICATION

- A long-term grease for greasing rolls and ball bearings.
- Furthermore, internal chain bearings, toothed and worm gears.
- All kinds of joints and couplings, machines and precision devices etc.
- The product is used for cleaning and protecting all kinds of chains and wire ropes in order to ensure easy and smooth running.
- Penetrates even to narrowest gaps. It's also appropriate for door-locks, door-hinges, slide bars, brake bars etc.
- Can safely be used in food processing areas.

USER INSTRUCTIONS

Remove at first soiling of the parts to be sprayed on and shake can well before use. Best results on cleaned surfaces.

FLEX LUBE X-TREME – FLX – 120

Art.no. 20111, 20113, 20117

Signature: JH

Date: 2023-08-18

This product information is property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company has to point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.

FLEX LUBE X-TREME

TECHNICAL DETAILS

Color:	Milky white
Packaging:	500 ml alu can aerosol. Art.no. 20111 300 ml alu can aerosol. Art.no. 20117 100 ml alu can aerosol. Art.no. 20113
Odor:	Characteristic.
Basic oil:	Mineral oil
Density (20°C):	0,85 g/ml
VOC:	20,0 %
Electric conductivity:	NT (not tested)
Shelf life (temp.) months (+5°C to +25 °C):	24 months.
Temperature resist:	-30°C to +250°C
Application & Surface temperature:	-10°C to +50°C
Certificates & Registrations:	GREEN WORLD, GREEN PROPELLANT, NSF (H1), Sunda Hus C-, BASTA, Byggsvarubedömningen accepted, Byggsvarudeklaration available.
Others:	In compliance with the legal regulations, please see current Material Safety Data Sheet. https://veidec.com/en/msds
User Instruction:	Scan the QR-code for MSDS, video and other information.



CERTIFICATES/REGISTRATIONS



GREEN WORLD, Has low impact on user and the environment.



GREEN PROPELLANT.



NSF; Category code H1. Reg. no: 156573. <http://www.nsf.com/USDA/letters/156573.pdf>



Sunda Hus, Assessment C-.



Flex Lube X-treme is registered by BASTA.

BYGGSVARUBEDÖMNINGEN Byggsvarubedömningen, accepted.

FEATURES



UP & DOWN.



Shake well before use.

FLEX LUBE X-TREME – FLX – 120

Art.no. 20111, 20113, 20117

Signature: JH

Date: 2023-08-18

This product information is property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company has to point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.